

Products Overview:	Connect IQ™ Intelligent Oven™ Professional Series Models PS301SS00, PS301SS01, PS302SS00, PS302SS01 Single & Double 30" Electric Wall Ovens			
General Warranty	Two Years Full Parts & Labor. Three Years Additional Limited on Selected Parts. Five Years Full Parts & Labor on Sealed Refrigeration (*).			
Upper / Lower & Single Oven Configuration:				
No. of Oven Racks	3 per oven			
No. of Rack Positions	5 per oven			
Bake Element	2000W Concealed			
Broiler Element	3300W, 10-Pass			
Convection Element	1650W with True European Convection			
Capacity	4.25 cu. ft			
Cleaning Ability	Easy-to-Clean Seamless Oven Cavity Surface			
Cleaning Method	Green Clean™ (Two-Hour Self-Clean: 1/2 Energy & 1/2 Time of Leading Brands)			
Heating Type	Standard Thermal			
Interior Dimensions	24 3/4" W x 15 3/4" H x 18" D			
Light(s) Location	Left & Right Sides of Oven Interior			
Light(s) Type	(2) 20W Halogen Lamps Per Oven (Consumer Replaceable)			
Temperature Management	Advanced Electronically Controlled Thermostat			
Upper / Lower Oven Safety:				
Access Control	Remote Access From Broadband Connected Windows PC Or Macintosh, Or Any Cell Phone, Or Any Telephone Land Line with Touch Tone			
Design	Safety Stops on All Racks			
Heating System	12-Hour Automatic Shut-Off			
	TOD (Thermally Operated Device) Safety			
Upper / Lower Oven Settings:				
Baking	Radiant Baking & Convection Baking			
Broiling	Radiant Broiling			
Convection	Radiant Convection, True European			
Roasting	Radiant Roasting & Convection Roasting			
Self-Cleaning	Delayed Self-Clean			
Lighting	Touch Screen Activated			
Specialized Cooking & Key Convenience Features:				
	Refrigeration (*)			
	Warm			
	Dehydration			
	Proofing			
	Temperature Sensing Meat Probe Settings (both ovens on dual models)			
	Internet-Connected, Remote Access			
	Accurate Time and Weather Display			
	My Favorites Settings			
	Cook Later Setting (*)			
	Delayed Cook (**)			
	LCD Touch Screen Control			
	Green Clean™ (Two-Hour Self-Clean: 1/2 Energy & 1/2 Time of Leading Brands)			
	Star-K Certified, Sabbath & Holiday Modes			
Oven(s) Controls:				
Clock/Timer	Electronic Clock Timer w/Keypad Entry; Live Updates From Internet			
Digital Display & User Interface	4" X 5 1/2" 3M™ NEC™ LCD Touch Screen			
Ease of Use	Touch Screen Controlled (No Physical Knobs or Dials)			
Kitchen Timer	Electronic Touch Controlled			
Lights Control	Touch Screen Activated; Door Activated			
Other Status Indicator	Audible Tones			
Overall Type	Advanced Electronic Controlled with LCD Touch Screen			
Styling:				
Oven Handles	Towel-Bar			
Oven Door Latch	Automatic Lock-In Self-Clean Cycle			
Oven Door	Drop-Down Fully Counterbalanced Swing & Lift Off (Removable)			
Quality Materials & Finishes:				
Exterior Finish	#304 Stainless Steel			
Oven Door	#304 Stainless Steel with Tempered Glass Window			
Oven Racks	Chrome Plated #304 Stainless Steel			
Door Handle End Caps	Chrome			
Oven/ Door Liner	Porcelain Enamel on Steel			
Oven Insulation	Aluminum-Faced Thermal Ceramic			
Dimensions PS302SS00:				
	Recessed:	Overall:		
Depth	23 1/2"	25"		
Height	59 5/8"	61 1/16"		
Width	28 1/2"	30"		
Dimensions PS302SS01:				
	Recessed:	Overall:		
Depth	23 1/2"	25"		
Height	50 3/16"	51 5/8"		
Width	28 1/2"	30"		
Dimensions PS301SS01:				
	Recessed:	Overall:		
Depth	23 1/2"	25"		
Height	28 3/16"	29 5/8"		
Width	28 1/2"	30"		
Dimensions PS301SS00:				
	Recessed:	Overall:		
Depth	23 1/2"	25"		
Height	37 5/8"	39 1/8"		
Width	28 1/2"	30"		
Cabinet Cutouts:				
	PS302SS00	PS302SS01	PS301SS00	PS301SS01
Depth, Opening	24"	24"	24"	24"
Height	60 1/2"	51 1/8"	38 9/16"	29 1/8"
Width	28 5/8"	28 5/8"	28 5/8"	28 5/8"
Power & Connectivity:				
Connection Type	Broadband Internet Connection Required (i.e., DSL, Cable, T1) in all functions available for a particular model.			
Electric Supply	240/208 VAC; 50A Service			
Total Connected Load	Double units 11.2 KW @ 240V 9.7 KW @ 208V Single Units 5.6 KW @ 240V 4.9 KW @ 208V			
Certification	CSA US Listed			
(*) Refrigerated Models Only		(**) Non Refrigerated Models		